NONLINEAR INTERNAL WAVES IN THE SOUTH CHINA SEA DURING ASIAEX

Antony K. Liu

NASA Goddard Space Flight Center, Greenbelt MD, USA

David T. Y. Tang

National Taiwan University, Taipei, Taiwan

and Steve R. Ramp

Naval Postgraduate School, Monterey CA, USA

OUTLINE:

- 0 Satellite Coverage and Analysis of RADARSAT SAR Images
- 0 Internal Wave Distribution Maps in SCS from SAR images during ASIAEX-2001
- 0 SAR and Mooring Data Comparison and Integration on May 9-10, and May 4-5, 2001
- 0 Environmental Parameters and Data Assimilation by Numerical Model
- 0 Wave-wave Interaction on May 18, and May 4, 2001 from SAR Imagery
- 0 Summary of the Characteristics of Internal Waves in SCS during ASIAEX
- 0 Implication of Internal Wave Effects on Acoustic Propagation

maintaining the data needed, and of including suggestions for reducing	llection of information is estimated to completing and reviewing the collect this burden, to Washington Headquuld be aware that notwithstanding a OMB control number.	tion of information. Send comments parters Services, Directorate for Info	regarding this burden estimate rmation Operations and Repor	e or any other aspect of ts, 1215 Jefferson Davis	this collection of information, s Highway, Suite 1204, Arlington					
1. REPORT DATE 01 DEC 2002		2. REPORT TYPE N/A		3. DATES COVE	RED					
4. TITLE AND SUBTITLE Nonlinear Internal	l Waves in the Soutl	5a. CONTRACT NUMBER N00014-99-1-0275								
		5b. GRANT NUMBER								
		5c. PROGRAM ELEMENT NUMBER								
6. AUTHOR(S)		5d. PROJECT NUMBER								
		5e. TASK NUMBER								
		5f. WORK UNIT NUMBER								
NASA Goddard Sj	ization name(s) and al pace Flight Center, Taiwan, Naval Pos	8. PERFORMING ORGANIZATION REPORT NUMBER								
9. SPONSORING/MONITO	ORING AGENCY NAME(S)	10. SPONSOR/MONITOR'S ACRONYM(S)								
				11. SPONSOR/M NUMBER(S)	ONITOR'S REPORT					
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited										
13. SUPPLEMENTARY NO Also See: M001452	OTES 2, The original docu	ment contains color	images.							
14. ABSTRACT										
15. SUBJECT TERMS										
16. SECURITY CLASSIFIC	CATION OF:		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON					
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	UU	14	RESI ONSIBLE FERSON					

Report Documentation Page


Form Approved OMB No. 0704-0188


Satellite Coverage and RADARSAT ScanSAR Images in SCS


- On January 25, 2001 ERS-2's gyro#1 failed, and Taiwan Ground Station can no longer process SAR images.
- In replacement, all cloud-free SPOT images (60km * 60km) with 20m resolution were collected and processed in near-real time during ASIAEX from Taiwan Ground Station.
- Most of days during ASIAEX, SPOT images were obscured by the cloud-cover and internal waves were visible only on May 7 and May 14, 2001.
- Four RADARSAT ScanSAR images (500km * 500km) from May 2, May 9, May 18, and May 11 (replaced by June 4) have been collected during ASIAEX through RADARSAT International.
- On May 11, due to transmission problem the SAR data were lost (Typhoon?).
- RADARSAT Standard SAR images (100km * 100km) from April 17, 18, 24 and May 1, 4, 5, 19, 26, 28, 2001 have been collected during ASIAEX through NRL and NOAA Satellite Active Archive (SAA).

Internal Wave Distribution Map from RADARSAT in the South China Sea during ASIAEX-2001

Antony K. Liu, NASA/GSFC









Transect A1B1

Transect A4B4





SUMMARY OF SAR AND MOORING DATA COMPARISON (May 9-10)

SENSOR (ADCP)	S2	S4	S5	S	6 S7	7 S8	SAR
DEPTH (m) DISTANCE (km)			18- 8.5	4 2' 12.9	75 35 12.0	0 800 88.1	
SHIFT TIME (min)			162 160	134 132	91 91	415 468	744
IW DIR (deg) MOOR DIR	75/85 16		45 16		5/5 25 .6 16	5 5	28
SHIFT DIST (km)	33.1		7.4	10.0	6.2	44.1	76
IW SPEED (m/s)	0.72 (0.33)		0.76 0.77			54)1.77 1.57 (1.75	
IW WIDTH (km)		0.7	1.5 1.6	1.		4 4 (0.7)	1.4 2.5
SOLITON #			3	,	*	5	3
IW LENGTH (km)		1.2	2.4-1.6 7.6-1.8			9.7-2.4 6.6 7.9-2.5	
CURRENT (m/s)	0.3	0.5 0.4	0.9 1.2			2 5	
AMPLITUDE (m)			(80/90) (32/6	53) (70/	95)	

SUMMARY

- O Satellite Remote Sensing Is Critical to Several Aspects of ASIAEX, Including Tracking Internal Waves, and Locating Fronts, Especially the Synoptic 2-D Internal Wave Pattern in the Test Area.
- O Comparison of RADARSAT ScanSAR and Mooring Data Show Good Agreement and Consistent Internal Wave Field with Marine Radar Images and Model Results on May 4-5, and 9-10, 2001.
- 0 Remote Sensing and Mooring Data Can Be Integrated by Numerical Simulations from Deep Ocean (SAR) to S5/6/7 (Mooring) on Shelf Using Modified KDV-Type Internal Wave Evolution Code.
- 0 Typical Internal Wave Characteristics:

Water Depth and Density:
 Internal Wave Direction:
 800 m to 70 m and CTD Data
 25° to 75° (Ray Tracing Method)

Internal Wave Speed: 1.7 m/s to 0.7 m/s
Soliton Width: 1.5 km to 0.7 km
Soliton Number: 5 to 3 to Wave Train


- Soliton Separation: 9.7 km and 2.4 km to Wavelength of 1.2 km

- Wave Amplitude: 95 m to 32 m

- Dissipation: Eddy Viscosity up to 5 m²/s

0 Wave-Wave Interaction Has Been Observed on May 4 and 18, 2001 in ASIAEX Test Area and Is Very Important for Acoustic Applications (Two-Dimensional Effects).

WAVE-WAVE INTERACTION



SUMMARY OF SAR AND MOORING DATA COMPARISON (May 4-5)

SENSOR (ADCP)	S2	S3	S4	S5	S6	S7	S8	SAR
DEPTH (m)								
DISTANCE (km)					12.9		88.1	
SHIFT TIME (min)			420	67 59				744
IW DIR (deg)	90	80	75	55	*			13
_					5* 5	25		10
MOOR DIR SHIFT DIST (km)				16 8.0	5 16	16	16	
Sim i Disi (Kiii)	13	.0			8.5	6.2	38.6	56
IW SPEED (m/s)	(0.35)		0.75		1.21 7) (1.18			
	(0.33)		1				.47 (1.55)	1.26
					0) (1.63)			
IW WIDTH (km)			0.7			0.8	0.8	1.5
				(0.8)			(0.7)	
SOLITON #	Packet		3	2	3	1	1	2
IW LENGTH (km)	0.2		1.3-1.0	2.1	1.9-1.5			2.0
CURRENT (m/s)				0.3	0.3	0.3		
	0.3		0.5	0.7	0.6	0.5		
AMPLITUDE (m)					(16/32))		
* Effects of Wave-W	Vave In	teracti	on					

MODEL OF NONLINEAR INTERNAL WAVE EVOLUTION ON SHELF

0 Evolution Equation of Wave Amplitude A (x,t) with Variable Coefficients

$$A_t + C_0 A_x + aAA_x + bA_{xxx} - eA_{xx} = 0$$
, $U(z) = C_0 A_0 f'(z)$

0 Eigen-Value Problem for Vertical Modes

$$f'' + [N^2 - w^2]f/C_o = 0$$
, $f(o) = f(-H) = 0$, $C_o = w/k$

0 Environmental Parameters

Nonlinear:
$$\mathbf{a} = 3C_o \int_{-H}^{0} \mathbf{f'}^3 dz / 2 \int_{-H}^{0} \mathbf{f'}^2 dz$$

Dispersion:
$$\mathbf{b} = \int_{-H}^{0} \mathbf{f}^2 dz / 2 \int_{-H}^{0} \mathbf{f}^2 dz$$

Dissipation: **e** - Eddy Viscosity

0 Numerical Simulations


- FFT in Spatial Coordinate

- Centered Divided Difference for Time Derivative

- Window Filter at the Computation Boundary

- Initial Waveform as Inputs from Field Data

NUMERICAL SIMULATION OF WAVE EVOLUTION



ACOUSTIC IMPACT OF INTERNAL SOLITONS

0 Resonance Coupling Effect

- Strong Horizontal Gradient in Sound Speed Induced by Internal Solitons
- Coupling between Acoustic Normal Modes

0 Time Spreading

- Differences in Acoustic Modal Group Velocities Cause Time Spreading of Pulses.
- Interference Patterns between Mode Multipaths Are Very Sensitive to Coupling Events.
- Significant Temporal Variation in Arrival-Time

0 Transmission Attenuation

- Coupling of Mode-1 into Higher Modes due to Soliton Packet
- In General, Attenuation Is Greater for Higher Modes
- Energy Sink and Significant Variability in Apparent Attenuation for Low Modes

0 Internal Soliton Parameters

- Soliton Number, Soliton Location, Soliton Direction, Soliton Wavelength, and Wave Packet Length
- More Soliton Activity Closer to Receiver, the Greater the Spreading and Bias in Arrivals

0 Two-Dimensional Effects

- Variability of Environmental and Soliton Parameters on Shelf in the ASIAEX Area
- Soliton Evolution Path Is not Aligned with Source and Receiver
- Wave-Wave Interaction